

KT-B03 Motion Dedector

Product's Instruction

Performance

- it can be used with all alarm system
- it fits different condition against mis-report or failed report by setting.
- LED can be set on or off when alarm.
- LED is off when waiting.
- Detect range is 10M radii and 90 degree of sector area.
- it is with temperature compensate circuit and it is nearly invariableness of sensitive.



Technology diamentions

- 1 Operating voltage 9.5VDC~14.5VDC
- 2 Supply voltage ripple 3.0Vpp@ 12VDC
- 3 Standby current 16mA
- 4 Current in alarm 20mA
- 5 Operating temp. 0 Degree Celsius ~50 Degree Celsius
- 6 Storage temp. -40 Degree Celsius ~60 Degree Celsius
- 7 Operating humidity 5~95% RH.
- 8 Storage humidity up to 99% RH.
- 9 RF immunity 10V/m with 80% AM from 80MHz~1GHz
- 10 Static immunity 8kV contact 15kV air
- 12 Transient immunity 2.4kV@ 1.2 joules
- 13 Walk detection speed 0.15~3.0 m/s
- 14 Coverage angle 75°(Min.)/90°(Max.)
- 16 Mounting heights 1.8~3.2M

Detail specification

HEAD QUARTER :

Address : No.25 Baoyuan Road Dongqian Lake Industry Area ,Dongqian Town Ningbo City / CHINA
Phone : 0086 574 88366066 - **Fax** : 0086 574 88327726

KEST TURKEY :

Address : İstoç 37 Ada No:5 Bağcılar / İSTANBUL
Phone : +90 (212) 659 50 98 - (212) 659 45 29 - **Fax** : +90 (212) 659 39 77