



ELECTRICAL CHARACTERISTICS:

CONTACT CURRENT RATING: 1 AMPERES.
 DIELECTRIC WITHSTANDING VOLTAGE: AC 500V R.M.S
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT DC 500V.
 CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM.
 OPERATING TEMPERATURE: -55°C TO +105°C.

MECHANICAL CHARACTERISTICS:

CONTACT INSERTION FORCE: 6.0 KG MAXIMUM.
 CONTACT SEPARATION FORCE: 1.0 KG MINIMUM.

MATERIALS:

CONTACT: BRASS.
 INSULATOR: P.B.T. UL 94-V0 RATED.
 SHELL: COLD ROLLED STEEL.

FINISHES:

CONTACTS: GOLD FLASHED 1U", 3U", 5U", 10U", 15U", 30U".
 SHELL: NICKEL, TIN OR GOLD PLATED.



煜倫有限公司

PART NO. USB-PS-4A

DWG NO. USB-PS-4A

FILE NO. HC-030

UNIT / mm

SCALE 1 : 1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X
 .XX
 .XXX
 AWG

DESCRIPTION:

U.S.B. A TYPE SOLDER (M) 半圓端子

AREA

REVISIONS

HK

DATE