



P.C.B. LAYOUT

Note:

- 1.Material:
 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
 1.2 Contact: Copper alloy,t=0.25mm
 1.3 Shell: Spcc,t=0.30mm

- 2.Specification:
 2.1 Current rating: 1 A Max.
 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 2.3 Contact resistance: 30 mΩ Max.
 2.4 Insulation resistance: 1000 MΩ Min.
 2.5 Total mating force: 4.0 Kgf Max.
 2.6 Total unmating force: 1.0 Kgf Min.
 2.7 Temperature range: -55°C~85°C

MORETHANALL
CONNECTORS
ASSEMBLIES

焯倫有限公司

| | |
|-----------|-----------|
| PART NO. | USB-SD-4B |
| DWG NO. | USB-SD-4B |
| FILE NO. | |
| UNIT / mm | SCALE 1:1 |

| | |
|------------|----|
| CHECKED BY | CY |
| DRAWING BY | |
| PROJECTION | |

| |
|----------------|
| TOLERANCES ARE |
| .X ± 0.3 |
| .XX ± 0.2 |
| .XXX ± 0.1 |
| AWG |

| | | | | |
|---------------|-------------------------|----|------|--|
| DESCRIP TION: | USB-B TYPE P.B.C(F)180° | | | |
| AREA | REVISIONS | HK | DATE | |